

# ProMinent Motorised metering pump type "PLASMA"



## Upto a capacity of 400 l/h

ProMinent Plasma pumps are motor driven diaphragm type pumps. These pumps are compact, consume low power and very reliable. These pumps are available upto a

capacity of 400 l/hr and the liquid ends are available in PVC, Polypropylene, Teflon and Stainless Steel.

## Your benefits

Plasma pumps are very compact, highly accurate and offer a reliable and long service to the customer.

## Field of application

- waste water treatment
- process water
- acid dosing
- chlorine dosing
- SMBS dosing

# ProMinent Motorised metering pump type "PLASMA"

## Technical Data

with motor 0.18 kW / 0.37 kW, 1440 rpm, 415 V, 50 c/s

Pump type	Delivery rate at max. back pressure			Stroke rate strokes/min	Suction lift m WC	Connection size G – DN	Motor rating kW	Shipping weight kg (PP/SS)
	bar	l/h	ml/stroke					
10010	10	10	1.4	115	3	8 x 5 mm	0.18	11 / 12
10015	10	15	1.7	150	3	8 x 5 mm	0.18	11 / 12
10020	10	20	3.6	115	3	1 1/4" – 20	0.18	11 / 12
10030	10	30	3.9	150	3	1 1/4" – 20	0.18	11 / 12
05050	5	50	7.2	115	3	1 1/4" – 20	0.18	12.1 / 14.5
05065	5	65	7.2	150	3	1 1/4" – 20	0.18	12.1 / 14.5
05090	5	90	13.0	115	3	1 1/4" – 20	0.18	12.1 / 14.5
05120	5	120	13.3	150	3	1 1/4" – 20	0.18	12.1 / 14.5
05200	5	200	29.0	115	3	1 1/4" – 20	0.18	12.1 / 14.5
05260	5	260	29.0	150	3	1 1/4" – 20	0.18	12.1 / 14.5
05300	5	300	43.5	115	3	1 1/4" – 20	0.37	14.5 / 16.9
05400	5	400	44.4	150	3	1 1/4" – 20	0.37	14.5 / 16.9